Library

Loc





Bookmarks

US Patent and Trademark Office

Notes

Recent Searches ▼ Search E-Mail View Notes Add Note Add Bookmark

Table of

Reader

Reviews

Academic

Errata

Current Book Hide Go Code Fragments only

Desktop

▼ Table of Contents



Advanced Search

Home

Essential SNMP

- Copyright
- ⊕ What Is SNMP?
- NMS Architectures
- SNMP-Compatible Hardware
- Metwork-Management Softwa
- Configuring Your NMS
- Configuring SNMP Agents
- Polling and Setting
- ⊕ Traps
- Extensible SNMP Agents
- Environment
- **⊞** MRTG
- Using Input and Output Octet
- More on OpenView's NNM
- **⊞**-SNMP RFCs
- SNMP Support for Perl
- **⊞**-SNMPv3
- Colophon
- Index

Browse By Category

View All Titles

⊕-Applied Sciences

Essential SNMP

By Douglas Mauro, Kevin Schmidt

Recent Pages

Publisher : O'Reilly Pub Date : July 2001

: 0-596-00020-0

Pages : 326 'Slots : 1.0

Contents Index Reviews Examples

This practical guide for network and system administrator SNMP along with the technical background to use it effect main focus is on practical network administration: how to agents and network management stations, how to use SNI modify variables on network devices, how to configure m software to react to traps sent by managed devices. Cover versions through SNMPv3.

URL http://proquest.safaribooksonline.com/0596000200

e c

ec

- **⊞** Business
- Certification
- **⊞**-Computer Science
- ⊕ Databases
- ⊕ Desktop Applications
- ⊕ Desktop Publishing
- **⊞**-E-Business
- **⊞**-E-Commerce
- ⊕ Enterprise Computing
- Graphics
- **⊞**-Hardware
- Human-Computer
 Interaction
- Internet/Online
- **⊞**-IT Management
- **⊞** Multimedia
- Networking
- Operating Systems
- Programming
- **⊞**-Security
- **⊞**-Software Engineering

Find a Specific Book

- Author
- ISBN
- Title
- Publisher

About Safari | Terms of Service | Privacy Policy | Contact Us | Help |

Copyright © 2002 Safari Tech Books Online. All rights reserved.

75 Arlington Street, Floor 3 Boston, MA 02116 1-800-889-3358

e

h e f b e c e ec e

Loc





Bookmarks

US Patent and Trademark Office Library

Book Title A 7

Essential SNMP

Kevin Schmidt

Table of Contents

By Douglas Mauro,

▼ Search snmp Go

Desktop

Code Fragments only

Advanced Search

Home

■ Browse By Category

Matching Categories

⊞ Networking (226)

- ⊕ Security (31)
- Storage Area
- Network (20)
- Cisco (19)
- More...

⊞ Operating Systems (140)

- **⊞**-Linux (35)
- ⊞-Windows 2000 (28)
- 田-UNIX (21)
 - More...

⊞ Certification (97)

- ⊕ Cisco (56)
- ⊕ Microsoft (20)
- ⊕-Sun (5)
 - More...

View All Categories...

View All Titles

- Artificial Intelligence
- ⊕ Business
- Certification
- Computer Science
- Databases
- ⊕ Desktop Applications
- Desktop Publishing
- **⊞** ·E-Business
- **⊞**-E-Commerce
- Enterprise Computing
- ⊕-Graphics
- Human-Computer Interaction
- ⊞-Internet/Online
- Markup Languages

Found 3525 section(s) in 604 book(s) that match your search for "snmp". **View by Section**

Recent Searches



Recent Pages

Hide Bookcovers Books 1 to 10 of 604 | Previous

Notes

Most Relevant Section:

Rel △♥

- 會會會 1. Essential SNMP
 - 2. SNMPv1 Protocol
 - 3. A Closer Look at SNMP



1

Open Source Network Administration By James Kretchmar Table of Contents

1. SNMP

- 2. Maintaining SNMP Tools
- 3. Installing SNMP Tools



PHP Developer's Cookbook, Second Edition By Sterling Hughes **Table of Contents**

- 1. Working with SNMP Object
- 2. Going Outside PHP
- 3. Introduction



TCP/IP Illustrated, Volume 1: The Protocols By W. Richard Stevens **Table of Contents**

1. SNMP: Simple Network Management Protocol

- 2. ISODE SNMP Manager and (Chapter 25)
- 3. Summary



Special Edition Using TCP/IP, Second Edition By NIIT **Table of Contents**

1. Simple Network Manageme Protocol (SNMP)

- 2. Summary
- 3. Network Management



7

BEA WebLogic Server™ Administration Kit By Scott Hawkins **Table of Contents**

- 1. Monitoring
 - 2. Configuring SNMP
 - 3. SNMP

Solaris™ 8 System Administrator's Reference

By Janice Winsor **Table of Contents**

1. Solstice Enterprise Agents SNMP Daemon (SUNWmibii)

> 2. Solstice Enterprise Agents Desktop Management Interfa

(SUNWsadmi)

e c

- ⊕ Multimedia
- Networking
- ⊕ Operating Systems
- Programming
- Security
- ⊕ Software Engineering

Find a Specific Book

- Author
- ISBN
- Title
- Publisher





Solaris™ 8 Network Administrator Certification Training Guide By Rafeeq Rehman Table of Contents

on

Network Management Too

2. INTRODUCTION

Master Agent

3. Network Management with

3. snmpdx — Sun Solstice En



Hardening Cisco Routers By Thomas Akin Table of Contents 1. SNMP Security Checklist

2. SNMP

3. SNMP Management Server



Cisco® Router Configuration & Troubleshooting, Second Edition
By Mark Tripod
Table of Contents

Router Monitoring

2. Conclusion

3. Collecting Data via SNMP

Books 1 to 10 of 604 | Previous

About Safari | Terms of Service | Privacy Policy | Contact Us | H

Copyright © 2002 Safari Tech Books Online. All rights res

75 Arlington Street, Floor 3

Boston, MA 02116

1-800-889-3358

IEEE HOME | SEARCH, IEEE | SHOP | WEB ACCOUNT | CONTACT IEEE



Membership Publica	ations/Services Standards Conferences Careers/Jobs
IEEE >	Welcome United States Patent and Trademark Office
Help FAQ Terms IEE	RE Peer Review Quick Links Se
Welcome to IEEE Xplores O- Home O- What Can I Access? O- Log-out	Your search matched 0 of 1114101 documents. A maximum of 500 results are displayed, 15 to a page, sorted by Relevance Descending order. Refine This Search:
Tables of Contents	You may refine your search by editing the current search expression or enterinew one in the text box.
O- Journals & Magazines O- Conference Proceedings O- Standards	pdu <and>packet<and>mib Check to search within this result set Results Key:</and></and>
Search - By Author - Basic - Advanced - CrossRef	JNL = Journal or Magazine CNF = Conference STD = Standard Results: No documents matched your query.
Member Services - Join IEEE - Establish IEEE - Web Account - Access the - IEEE Member - Digital Library	
O- Access the IEEE Enterprise File Cabinet	

Print Format

Home | Log-out | Journals | Conference Proceedings | Standards | Search by Author | Basic Search | Advanced Search | Join IEEE | Web Account |
New this week | OPAC Linking Information | Your Feedback | Technical Support | Email Alerting | No Robots Please | Release Notes | IEEE Online
Publications | Help | FAQ| Terms | Back to Top

Copyright © 2004 IEEE — All rights reserved

h eee e eee g e ch e ch e

С

e

IEEE HOME | SEARCH IEEE | SHOP | WEB ACCOUNT | CONTACT IEEE



Publications/Services Standards Conferences Welcome **United States Patent and Trademark Office** » Se: **Quick Links** FAQ Terms IEEE Peer Review Welcome to IEEE Xplore* Home Your search matched 20 of 1114101 documents. — What Can A maximum of **500** results are displayed, **15** to a page, sorted by **Relevance** I Access? Descending order. O- Log-out Refine This Search: **Tables of Contents** You may refine your search by editing the current search expression or enterior ()- Journals new one in the text box. & Magazines Search pdu<and>packet ()- Conference ☐ Check to search within this result set **Proceedings** O- Standards **Results Key: JNL** = Journal or Magazine **CNF** = Conference **STD** = Standard Search O- By Author ()- Basic 1 Performance of ATM and variable length packet access in broadbance and wireless networks — Advanced Sriram, K.; ()- CrossRef Universal Personal Communications, 1998. ICUPC '98. IEEE 1998 Internationa Conference on , Volume: 1 , 5-9 Oct. 1998 **Member Services** Pages:495 - 501 vol.1 O- Join IEEE [Abstract] [PDF Full-Text (676 KB)] **IEEE CNF** - Establish IEEE Web Account 2 Frame loss due to buffer overflows in fast packet networks O- Access the Bhargava, A.; Hluchyj, M.G.; **IEEE Member Digital Library** INFOCOM '90. Ninth Annual Joint Conference of the IEEE Computer and Communication Societies. 'The Multiple Facets of Integration'. Proceedings., IEEE Enterprise IEEE , 3-7 June 1990 Pages:132 - 139 vol.1 O- Access the **IEEE Enterprise** File Cabinet [Abstract] [PDF Full-Text (552 KB)] IEEE CNF 3 Optimal packet size via marginal utility image compression and Print Format expansion delay minimization for theater of war and theater missile defense: congestion controlled combination protocol Niznik, C.A.; Military Communications Conference Proceedings, 1999. MILCOM 1999. IEEE , Volume: 1 , 31 Oct.-3 Nov. 1999 Pages: 266 - 270 vol.1

4 Jitter reduction in CBR HDTV transport stream packet communicatio over lossy ATM network

[Abstract] [PDF Full-Text (512 KB)]

IEEE CNF

Jong Moo Sohn; Jong Ick Lee; In Hwa Hong; Byung Ryul Lee; Moon Key Lee; Computer Communications and Networks, 1998. Proceedings. 7th Internation Conference on , 12-15 Oct. 1998

Pages:12 - 19

[Abstract] [PDF Full-Text (883 KB)] IEEE CNF

5 End-to-end modeling and simulation of MPEG-2 transport streams of ATM networks with jitter

Wenwu Zhu; Hou, Y.T.; Yao Wang; Ya-Qin Zhang;

Circuits and Systems for Video Technology, IEEE Transactions on , Volume:

8, Issue: 1, Feb. 1998

Pages:9 - 12

[Abstract] [PDF Full-Text (76 KB)] IEEE JNL

6 TAP: architecture for trusted transfers in ATM networks with active switches

Gonzalez-Sanchez, J.L.; Domingo-Pascual, J.;

High Performance Switching and Routing, 2000. ATM 2000. Proceedings of the IEEE Conference on , 26-29 June 2000

Pages: 105 - 112

[Abstract] [PDF Full-Text (640 KB)] IEEE CNF

7 Performance issues of ATM multicasting based on per-PDU ID assignment

Mangues-Bafalluy, J.; Domingo-Pascual, J.;

Communications, 2000. ICC 2000. 2000 IEEE International Conference

on , Volume: 3 , 18-22 June 2000

Pages:1733 - 1737 vol.3

[Abstract] [PDF Full-Text (440 KB)] IEEE CNF

8 Throughput of Hybrid ARQ Types for UTRA TDD mode

Slanina, P.; Raji, F.; Mecklenbrauker, C.; Holzl, C.; Ostermayer, G.; Stadler, T.

EUROCOMM 2000. Information Systems for Enhanced Public Safety and Secur IEEE/AFCEA , 17 May 2000

Pages:11 - 15

[Abstract] [PDF Full-Text (536 KB)] IEEE CNF

9 MPEG-2 over ATM: system design issues

Varma, S.;

Compcon '96. 'Technologies for the Information Superhighway' Digest of Papers , 25-28 Feb. 1996

Pages:26 - 31

[Abstract] [PDF Full-Text (444 KB)] IEEE CNF

10 On the MAC performance of self-organizing broadband multihop multimedia wireless networks

Walke, B.; Bangnan Xu;

Vehicular Technology Conference, 2001. VTC 2001 Fall. IEEE VTS 54th , Volur 2 , 7-11 Oct. 2001

Pages:982 - 986 vol.2

[Abstract] [PDF Full-Text (432 KB)] IEEE CNF

11 Simulating MPEG-2 transport stream transmission over wireless AT Kassler, A.; Schirpf, O.;

Acoustics, Speech, and Signal Processing, 1999. ICASSP '99. Proceedings., 19 IEEE International Conference on , Volume: 6 , 15-19 March 1999 Pages: 3057 - 3060 vol.6

[Abstract] [PDF Full-Text (384 KB)] IEEE CNF

12 Simple data link (SDL) protocol: an efficient and low complexity dailink protocol for high-speed packet networks

Doshi, B.; Dravida, S.; Hernandez-Valencia, E.;

Global Telecommunications Conference, 1999. GLOBECOM '99, Volume: 2, 1 Pages:1295 - 1301 vol.2

[Abstract] [PDF Full-Text (532 KB)] IEEE CNF

13 A simulation study of two-level forward error correction for lost parecovery in B-ISDN/ATM

Oguz, N.C.; Ayanoglu, E.;

Communications, 1993. ICC 93. Geneva. Technical Program, Conference Reco IEEE International Conference on , Volume: 3 , 23-26 May 1993

Pages: 1843 - 1846 vol. 3

[Abstract] [PDF Full-Text (376 KB)] IEEE CNF

14 Mapping with cell addressing of train transport MPEG-2 over ATM c via AAL-5

Aghaei Nia, H.; Gazalet, M.; Rouvaen, J.M.;

Electronics Letters, Volume: 32, Issue: 20, 26 Sept. 1996

Pages:1857 - 1858

[Abstract] [PDF Full-Text (300 KB)] IEE JNL

15 Modeling and simulation of MPEG-2 video transport over ATM network considering the jitter effect

Wenwu Zhu; Hou, Y.T.; Yao Wang; Ya-Qin Zhang;

Multimedia Signal Processing, 1997., IEEE First Workshop on , 23-25 June 199

Pages:401 - 406

[Abstract] [PDF Full-Text (264 KB)] IEEE CNF

1 2 Next

Home | Log-out | Journals | Conference Proceedings | Standards | Search by Author | Basic Search | Advanced Search | Join IEEE | Web Account |
New this week | OPAC Linking Information | Your Feedback | Technical Support | Email Alerting | No Robots Please | Release Notes | IEEE Online
Publications | Help | FAQ| Terms | Back to Top

Copyright © 2004 IEEE — All rights reserved

IEEE HOME | SEARCH IEEE | SHOP | WEB ACCOUNT | CONTACT IEEE

Membership Publications/Services Standards Conferences Careers/Jobs



Help FAQ Terms IEE	Welcome United States Patent and Trademark Office E Peer Review Quick Links Welcome United States Patent and Trademark Office **See The Peer Review Quick Links The Peer Review The Peer Review The Peer Review Quick Links The Peer Review The
Welcome to IEEE Xplore* - Home - What Can I Access? - Log-out	Your search matched 1 of 1114101 documents. A maximum of 500 results are displayed, 15 to a page, sorted by Relevance Descending order. Refine This Search:
Tables of Contents - Journals & Magazines - Conference Proceedings - Standards	You may refine your search by editing the current search expression or enterinew one in the text box. pdu <and>mib</and>
Search O- By Author O- Basic O- Advanced O- CrossRef Member Services	<pre>1 Using SNMP to manage networks Drake, P.; Designing Resilient Architectures, IEE Colloquium on , 15 Nov 1991 Pages:2/1 - 2/4 [Abstract] [PDF Full-Text (228 KB)] IEE CNF</pre>
O- Join IEEE O- Establish IEEE Web Account O- Access the IEEE Member Digital Library	[ABSTRACT TO THE TEXT (225 KB)] THE CHI
O- Access the IEEE Enterprise File Cabinet	

Print Format

Home | Log-out | Journals | Conference Proceedings | Standards | Search by Author | Basic Search | Advanced Search | Join IEEE | Web Account |
New this week | OPAC Linking Information | Your Feedback | Technical Support | Email Alerting | No Robots Please | Release Notes | IEEE Online
Publications | Help | FAQ | Terms | Back to Top

Copyright © 2004 IEEE — All rights reserved



CiteSeer Find: MIB group table snmp

Documents *

· Citations

Searching for PHRASE mib group table snmp.

Restrict to: Header Title Order by: Expected citations Hubs Usage Date Try: Google (CiteSeer) Google (Web) Yahoo! MSN CSB DBLP

No documents match Boolean query. Trying non-Boolean relevance query. 500 documents found. Order: relevance to query.

Management of Broadband Networks Using a 3D Virtual World - Crutcher, Lazar, Feiner. (1993) (Correct) (3 citations)

as existing inside a Management Information Base (MIB)Access to other planes would occur via (IRM) 1]This model has been developed by our group to provide a network-independent view of the a mixture of abstractions including icons, graphs, tables, and textual reports. While this is a huge ftp.ctr.columbia.edu/CTR-Research/comet/public/papers/95/CRU95.ps.qz

Design and Implementation of TMN SMK System Using CORBA ORB - Park, Ha, Hong (1998) (Correct) (2 citations)

protocol for obtaining the SMK information from MIB and for SMK context negotiations. Also, our effort Standard 10040, 1991. 5. Open Management Group, The Common Object Request Broker: Architecture characteristics that we believe are important. Table I shows the performance results of binding times amazon.postech.ac.kr/papers/JNSM/JNSM96/jnsm-smk-corba.pdf

Interaction of a TMN-oriented Network Management Platform with a.. - Calisti (1998) (Correct) managers and Management Information dataBase (MIB)In addition an agent may spontaneously generate (the Management Information Database (MIB) for SNMP or the Guidelines Objects Model (GOM) for CMIP) liawww.epfl.ch/~calisti/noc98.ps.gz

Generic Templates for TMN Case Representation - Ramos, Alves, Santos (Correct) as managed objects in a Management Information Base (MIB) Fig. 1) Fig. 1. TMN Model Inside the TMN storage and retrieve, the management cases are grouped in class and the relationship of these classes wwwagr.informatik.uni-kl.de/~lsa/gwcbr99/alexandre_ramos.ps.gz

Dynamic Management of Internet Telephony Servers: A Case.. - Keller, Reiser (1999) (Correct) and 20 tables the TIS management information base (MIB) defines 6 types of asynchronous event messages. receive event notifications from peers and can be grouped together in order to jointly achieve a task. kbytes and consists of about 150 variables and 20 tables the TIS management information base (MIB) www.nm.informatik.uni-muenchen.de/common/Literatur/MNMPub/Publikationen/kere99/Postscript-Version/kere99.ps.gz

Databases for Active, Rapidly Changing data Systems - Datta, Viguier, Orer (1996) (Correct) database is called a Management Information Base (MIB)The importance of this database is underscored unified ARCS scenario to the large and disparate groups of researchers and practitioners who work on ratios on the outputs of switches, and routing tables. In a chemical process control domain control loochi.bpa.arizona.edu/pub/publications/cacm.ps.gz

S.A.R.I.: An Object Oriented High Speed MultiNetwork.. - Znaty (Correct)

is introduced: the management information base (MIB)Indeed a MIB is present for every protocol and related management functions need to be grouped. To reach this objective, a layered management Moreover, the relay interface implements a mapping table. This table enables the gateway to record the www.rennes.enst-bretagne.fr/~znaty/papers/JNSM 95.ps

On a Rule Based Management Architecture - Koch, Krämer, Rohde (1995) (Correct) (8 citations) the task being executed one object can be in both groups at different times. Management activities are pages 433-453. Addison-Wesley, 1994.

snmp.cs.utwente.nl/bibliography/articles/general/index.h snmp.cs.utwente.nl/bibliography/articles/general/koc9501.ps

Report of the EAGLES Workshop on Implemented.. - Backofen, Krieger, .. (1993) (Correct) (2 citations) 1 Contents 1 Introduction 3 1.1 The Working Group:

c e ee b e С aimed at make these activities better known (round-tables, workshops, conferences) 4 Introduction ffl ftp.tcs.informatik.uni-muenchen.de/pub/backofen/publ/EAGLES-WS-Implemented93.ps.gz

On the Homotopy Type of the Spectrum Representing Elliptic.. - Baker (1989) (Correct) (2 citations) E X 2 Andrew Baker Modular Forms For The Modular **Group** SI 2 (z)We Remark That The Author's Earlier www.maths.gla.ac.uk/~andy/dvi-ps/homell.ps

<u>Undoing Actions in Collaborative Work - Prakash, Knister (1992) (Correct) (23 citations)</u> system. Numerous collaborative editors and other **group** applications have been constructed, such as GROVE ftp.sunet.se/pub/groupware/DistEdit/papers/undo tech report.ps.gz

Coordination and Tailorability Issues in the design of a.. - Domingos, Martins (1997) (Correct) Issues in the design of a Generic Large Scale **Group**ware Platform Henrique Joo L. Domingos Jos A. asc.di.fct.unl.pt/~hj/papers/97/group97-tailorability.ps.gz

<u>Kernel-Level Threads for Dynamic, Hard Real-Time Environments - Marty Humphrey (1995)</u> (Correct) (3 citations)

to specify key properties of threads and thread **groups**. For a thread, this includes whether or not the this is that the context switch cost appears high. **Table** 1 gives the times for the various operations of counter.cs.umd.edu/~rich/courses/cmsc818G-s98/papers/spring_kernel.ps

Spaces of Null Homotopic Maps - Dwyer, Wilkerson (1989) (Correct) (1 citation) maps from B to X when is a locally finite **group**, and other components of the mapping space when hopf.math.purdue.edu/pub/Dwyer-Wilkerson/nullmaps/nullmaps.ps.gz

Toric Varieties and Algebraic Monoids - Neeb (1992) (Correct)

Let K be a field and K Gm the multiplictive **group** of K viewed as an algebraic **group** over K .A K www.math.helsinki.fi/EMIS/journals/JLT/vol.2_no.2/neeb2pl.ps

Quaquaversal Tilings And Rotations - Conway, Radin (1995) (Correct) (1 citation) structure of the tiling we are led to determine the **group** G(mn) generated by such a pair of rotations, mpej.unige.ch/mp_arc/e/95-425.ps

<u>Designing Parallel Programs by the Graphical Language GRAPNEL - Eter Kacsuk (1996)</u> (Correct) (15 citations)

paradigm. GRAPNEL supports graphically the Process **Group** abstraction and the automatic generation of www.kfki.hu/~mszkihp/info/ParComp/papers/EuroMicroPSE-grapnel.ps.Z

Tcl/Tk, Tkined, and Network Management - Hamann (1996) (Correct)

Scotty Includes Its Own **Snmp** Protocol Stack, A **Snmp Mib** Parser As Well As A Gdmo **Mib** Parser And An Coordinating Efforts with Computer Science Research **Group** 12 6.6 Discovering Network Devices on Subnets to standard **mib**-2 requests, such as IP Routing **Table** snapshots and Interface Loads. I applied some cashew.cs.tamu.edu/people/jhamann/entc485/report/toplevel.ps.Z

<u>Design Issues for an Adaptive Mobile Group Editor - Whalen (1997) (Correct) (2 citations)</u>
This Information Can Be Found In The **Snmp** Wavelan **Mib** [25]Which Has Not Yet Been Integrated With The Design Issues for an Adaptive Mobile **Group** Editor by Tara J. Whalen A thesis presented to ccnga.uwaterloo.ca/pub/papers/Ps/thesismas23.ps.Z

Web Based ATM PVC Management - van der Waaij, Sprenkels, van.. (1998) (Correct) switches from different vendors use proprietary MIBs, which implies that the tool must also support Management Protocol (SNMPv1)RFC1157 [3] NM Group, UTopia: The Web Based ATM Management tool, overview' and 'port statistics'generate tables. The two other functions have a more complex wwwsnmp.cs.utwente.nl/nm/research/results/publications/waaij/Eunice98CameraReady.pdf

First 20 documents Next 20

Try your query at: Google (CiteSeer) Google (Web) Yahoo! MSN CSB DBLP

CiteSeer.IST - Copyright Penn State and NEC

hceee ec g be



Groups New! <u>Images</u> News Froogle more »

site:citeseer.ist.psu.edu MIB group table sn Search

Advanced Search Preferences

Results 1 - 10 of about 46 from citeseer.ist.psu.edu for MIB group table snmp. (0.28 seconds)

Citations: - ed, Information, network, TCP, MIB, Request, Series ...

Sponsored Links

... Group (mcastInfo) was added to the standard MIB [16] in ... to store the multicast communication and 7 Table 1 Example of Multicast Group Information in ...

Tutorial on SNMP MIBs What you need on SNMP MIBs Pdf Guide to Remote Site Monitoring www.DpsTelecom.com

citeseer.ist.psu.edu/context/43817/0 - 39k - Cached - Similar pages

Citations: View-based Access Control Model - Wijnen, Presuhn ...

... IETF Network Working Group RFC 2275 (January ... have the right to read or modify specific parts of the MIB. ... A good example are SNMP access control tables [5] or IP ... citeseer.ist.psu.edu/context/1079590/0 - 11k - Cached - Similar pages

<u>Citations: NeMaC for IIS Accounting: User's Guide - Maiocchi ...</u>

... The work of the RTFM group provided a useful framework for the ... SNMP agent and stores the measured data in a meter MIB defined in ... and the flow table at the ... citeseer.ist.psu.edu/context/1215228/0 - 13k - Cached - Similar pages

<u>Citations: - Structure, Management, TCP, internets, RFC ...</u>

... Network Working Group, Request for Comments 1065, August 1988 ... of Counters The ATM Interface MIB defines all ... may have multiple instances, eg table entries, shall ... citeseer.ist.psu.edu/context/62432/0 - 36k - Cached - Similar pages

Citations: Traffic Flow Measurement: Meter MIB - Brownlee, Mills ...

... is a stand alone SNMP agent and stores the measured data in a meter MIB ... the Meter MIB proposed by the RTFM (Real Time Flow Monitoring) working group ... citeseer.ist.psu.edu/context/973357/0 - 24k - Cached - Similar pages

<u>Citations: An Architecture for describing SNMP Management ...</u>

... objects contained in the Management Information Base (MIB) Although network ... shows the table indexing structure ... The SNMP version 3 working group published SNMPv3 ... citeseer.ist.psu.edu/context/96476/0 - 20k - Cached - Similar pages

Unknown (ResearchIndex)

... 34 The Interfaces Group MIB (context) - McCloghrie, Kastenholz - 2000 ... 2 The Inverted Stack Table Extension to the Interfaces Group M.. ... citeseer.ist.psu.edu/666952.html - 18k - Cached - Similar pages

Unknown (ResearchIndex)

... Table of Contents 1 The SNMP Management Framework... (Update) ... 34 The Interfaces Group MIB (context) - McCloghrie, Kastenholz - 2000 ... citeseer.ist.psu.edu/685714.html - 17k - Cached - Similar pages

Citations: Definitions of Managed Objects for the Delegation of ...

... Internet Draft !draft- ietf-disman-script-mib-01.txt?, SNMP Research, ... [3] This working group produced among other things the DISMAN SCRIPT MIB, ... citeseer.ist.psu.edu/context/266824/0 - 30k - Cached - Similar pages

<u>Citations: Simple Network Management Protocol - Jeffrey, Case ...</u>

... A group of them have fixed values, and others like the one ... GetNext is a powerful

h g gec e ch ec e ee b e g

operation that allows MIB traversal and facilitates table entry accesses. ... citeseer.ist.psu.edu/context/642902/0 - 11k - Cached - Similar pages

Goooogle > 1 2 3 4 5 Next

Result Page:

Free! Google Desktop Search: Search your own computer.

site:citeseer.ist.psu.edu MIB grou Search

Search within results | Language Tools | Search Tips | Dissatisfied? Help us improve

Google Home - Advertising Programs - Business Solutions - About Google ©2005 Google

Unknown (Make Corrections) Network Working Group E. Bell Request for Comments: 2674 3Com Corp. Category:...

View or download: tzi.de/~cabo/pdfrfc/rfc2674.txt.pdf Cached: PDF PS.gz PS Image Update Help

CiteSeer Home/Search Bookmark Context Related

From: tzi.de/~cabo/pdfrfc/ (more) (Enter author homepages).

(Enter summary)

Rate this article: 1 2 3 4 5 (best) Comment on this article

Abstract: This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in TCP/IP based internets. In particular, it defines two MIB modules for managing the new capabilities of MAC bridges defined by the IEEE 802.1D-1998 MAC Bridges and the IEEE 802.1Q-1998 Virtual LAN (VLAN) standards for bridging between Local Area Network (LAN) segments. One MIB module defines objects for managing the 'Traffic Classes' and 'Enhanced Multicast Filtering' components of... (Update)

Active bibliography (related documents): More All

- 0.5: Unknown (Correct)
- 0.1: Network Working Group M. Daniele Request For Comments (Correct)
- 0.1: Network Working Group D. Raz Request For Comments (Correct)

Similar documents based on text: More All

- 0.1: Fiber Channel Over TCP/IP (FCIP) Rajagopal, Bhagwat, Helland, al. (2001) (Correct)
- 0.1: Resume Liao (Correct)
- 0.1: Estimating Small Cell-Loss Ratios in ATM Switches via.. L'Ecuyer, Champoux (Correct)

BibTeX entry: (Update)

```
@misc{ -unknown,
  title = "Unknown",
 url = "citeseer.ist.psu.edu/683718.html" }
```

Citations (may not include all citations):

- 436 Simple Network Management Protocol (context) Case, Fedor et al. 1990
- 309 Management Information Base for Network Management of TCP/IP.. (context) McCloghrie, Rose
- 241 Structure and Identification of Management Information for T.. (context) Rose, McCloghrie 1990
- 174 Concise MIB Definitions (context) Rose, McCloghrie 1991
- 173 Information processing systems Open Systems Interconnectio.. (context) processing, Systems et al. -1987
- 173 Information processing systems Open Systems Interconnectio.. (context) Information, Open et al. 1987
- 130 Protocol Operations for Version 2 of the Simple Network Mana.. (context) Case, McCloghrie et al. 1996
- 114 A Convention for Defining Traps for use with the SNMP (context) Rose 1991
- 110 An Architecture for Describing SNMP Management Frameworks (context) Harrington, Presuhn 1999
- 98 Message Processing and Dispatching for the Simple Network Ma.. (context) Case, Harrington et al. 1999
- 91 Structure of Management Information Version 2 (SMIv2 (context) McCloghrie, Perkins et al. 1999
- 89 The User-Based Security Model (USM) for Version 3 of the Sim.. (context) Blumenthal, Wijnen 1999
- 88 Textual Conventions for SMIv2 (context) McCloghrie, Perkins et al. 1999
- 87 Transport Mappings for Version 2 of the Simple Network Manag., (context) Case, McCloghrie et al. 1996
- 78 Introduction to Community-based SNMPv2 (context) Case, McCloghrie et al. 1996
- 75 Conformance Statements for SMIv2 (context) McCloghrie, Perkins et al. 1999
- 54 Introduction to Version 3 of the Internet-standard Network M., (context) Case, Mundy et al. 1999
- 43 IEEE Standards for Local and Metropolitan Area Networks: Vir., (context) IEEE 1998
- 27 SNMP Applications (context) Levi, Meyer 1999
- 27 The Interfaces Group MIB using SMIv2 (context) McCloghrie, Kastenholz 1997
- 20 View-based Access Control Model for the Simple Network Manag.. (context) Wijnen, Presuhn 1999
- 14 Definitions of Managed Objects for Bridges (context) Decker, Langille et al. 1993
- 2 Definitions of Managed Objects for Source Routing Bridges (context) Decker, McCloghrie et al. 1993
- 1 MAC Bridges (context) IEC, IEEE et al. 1993

Documents on the same site (http://www.tzi.de/~cabo/pdfrfc/): More

Network Working Group J. Touch Request for Comments: 1810 ISI .. - Status Of This (Correct) Unknown - (Correct)

Unknown - (Correct)

Online articles have much greater impact More about CiteSeer.IST Add search form to your site Submit documents Feedback

CiteSeer.IST - Copyright Penn State and NEC

h

436 citations found. Retrieving documents...

J. Case, M. Fedor, M. L. Schoffstall, and C. Davin. Simple Network Management Protocol. Technical report, internet-rfc, November 1996.

CiteSeer Home/Search Document Not in Database Summary Related Articles Check

This paper is cited in the following contexts:

First 50 documents Next 50

<u>Unknown - Self-citation (Case) (Correct)</u>

No context found.

Case, J., Fedor, M., Schoffstall, M. and Davin, J., "Simple Network Management Protocol", STD 15, RFC 1157, May 1990.

<u>Unknown - Self-citation (Case) (Correct)</u>

No context found.

Case, J., Fedor, M., Schöffstall, M., and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, SNMP Research, Performance Systems International, Performance Systems International, MIT Laboratory for Computer Science, May 1990.

<u>Unknown - The Simple Network</u> Self-citation (Case) (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M. and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, May 1990.

Networking Issues in Wireless Sensor Networks - Deepak Ganesan Alberto (Correct)

No context found.

J. Case, M. Fedor, M. L. Schoffstall, and C. Davin. *Simple Network Management Protocol*. Technical report, internet-rfc, November 1996.

Research Paper - Scalability Of Peer (Correct)

No context found.

J. Case, M. Fedor, M. Schoffstall, and J. Davin. *The simple network management protocol.* RFC1155, STD 16, 1990.

Unknown - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, SNMP Research, Performance Systems International, Performance Systems International, MIT Laboratory for Computer Science, May 1990.

<u>Unknown - (Correct)</u>

No context found.

h ceee e ce

Citations: Simple Network Management Protocol - Case, Fedor, Schoffstall, Davin (Rese... Page 2 of 7

Case, J., Fedor, M., Schoffstall, M. and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, May 1990.

Unknown - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M. and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, May 1990.

Unknown - Snmp Management Frameworks (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M. and J. Davin, "The Simple Network Management Protocol", STD 15, RFC 1157, May 1990.

Unknown - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol", RFC 1157, SNMP Research, Performance Systems International, Performance Systems International, MIT Laboratory for Computer Science, May 1990.

Unknown - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, SNMP Research, Performance Systems International, Performance Systems International, MIT Laboratory for Computer Science, May 1990.

Proceedings of 2000 USENIX Annual Technical Conference - San Diego California (2000) (Correct)

No context found.

J. D. Case, M. S. Fedor, M. L. Schoffstall, and C. Davin. Simple Network Management Protocol (SNMP). RFC 1157, May 1990.

Unknown - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, SNMP Research, Performance Systems International, Performance Systems International, MIT Laboratory for Computer Science, May 1990.

Unknown - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol", RFC 1157, SNMP Research, Performance Systems International, Performance Systems International, MIT Laboratory for Computer Science, May 1990.

<u>Unknown - (Correct)</u>

h ceee e ce

Citations: Simple Network Management Protocol - Case, Fedor, Schoffstall, Davin (Rese... Page 3 of 7

No context found.

Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, SNMP Research, Performance Systems International, Performance Systems International, MIT Laboratory for Computer Science, May 1990.

Unknown - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M. and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, May 1990.

Unknown - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, SNMP Research, Performance Systems International, Performance Systems International, MIT Laboratory for Computer Science, May 1990.

Network Working Group M. Rose Request for Comments: 1418.. - Status Of This (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, SNMP Research, Performance Systems International, Performance Systems International, MIT Laboratory for .Computer Science, May 1990.

<u>Unknown - Simple Network Management</u> (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M. and J. Davin, "The Simple Network Management Protocol", STD 15, RFC 1157, May 1990.

<u>Unknown - (Correct)</u>

No context found.

Case, J., Fedor, M., Schoffstall, M. and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, May 1990.

<u>Unknown</u> - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, May 1990.

Unknown - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M. and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, May 1990.

Network Working Group D. Cong M. Hamlen, Editors - Request For Comments (Correct)

h ceee e c e

Citations: Simple Network Management Protocol - Case, Fedor, Schoffstall, Davin (Rese... Page 4 of 7

No context found.

Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol", RFC 1157, May 1990.

Network Working Group F. Baker - Request For Comments (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, SNMP Research, Performance Systems International, Performance Systems International, MIT Laboratory for Computer Science, May 1990.

Unknown - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M. and J. Davìn, "Simple Network Management Protocol", STD 15, RFC 1157, May 1990.

A QoS Distributed Transport Architecture - Basto (2003) (Correct)

No context found.

Case, J., M. Fedor, M. Schoffstall, J. Davin, A Simple Network Management Protocol (SNMP), . 1990.

Unknown - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M. and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, May 1990.

<u>Unknown - (Correct)</u>

No context found.

Case, J., Fedor, M., Schoffstall, M. and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, May 1990.

Unknown - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M. and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, May 1990.

Unknown - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, SNMP Research, Performance Systems International, Performance Systems International, MIT Laboratory for Computer Science, May 1990.

Unknown - (Correct)

No context found.

h ceee e ce

Citations: Simple Network Management Protocol - Case, Fedor, Schoffstall, Davin (Rese... Page 5 of 7

Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol (SNMP), RFC 1157, SNMP Research, Performance Systems International, Performance Systems International, MIT Laboratory for Computer Science, May 1990.

Unknown - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol", RFC 1157, SNMP Research, Performance Systems International, Performance Systems International, MIT Laboratory for Computer Science, May 1990.

S-RIP: A Secure Distance Vector Routing Protocol - Wan, Kranakis, van Oorschot (Correct)

No context found.

J. Case, M. Fedor, M. Schoffstall, and J. Davin. *A Simple Network Management Protocol* (SNMP). RFC 1157. May 1990.

Unknown - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol", RFC 1157, SNMP Research, Performance Systems International, Performance Systems International, MIT Laboratory for Computer Science, May 1990.

Unknown - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M. and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, May 1990.

<u>Unknown</u> - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, SNMP Research, Performance Systems International, Performance Systems International, MIT Laboratory for Computer Science, May 1990.

<u>Unknown - (Correct)</u>

No context found.

Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, May 1990.

On Generic Scalability Problems in Monitoring of - Data Communication Networks (Correct)

No context found.

J. Case, M. Fedor, M. Scho stall, and J. Davin. A Simple Network Management Protocol (SNMP), May 1990. RFC 1157.

<u>Unknown - (Correct)</u>

h ceee e ce

Citations: Simple Network Management Protocol - Case, Fedor, Schoffstall, Davin (Rese... Page 6 of 7

No context found.

Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol (SNMP), RFC 1157, SNMP Research, Performance Systems International, Performance Systems International, MIT Laboratory for Computer Science, May 1990.

Unknown - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M. and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, May 1990.

Unknown - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M. and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, May 1990.

Unknown - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, SNMP Research, Performance Systems International, Performance Systems International, MIT Laboratory for Computer Science, May 1990.

<u>Unknown - (Correct)</u>

No context found.

Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol", RFC 1157, SNMP Research, Performance Systems International, Performance Systems International, MIT Laboratory for Computer Science, May 1990.

Programming Systems for Autonomy - Alexander Konstantinou Yechiam (2003) (Correct)

No context found.

J. Case, M. Fedor, M. Schoffstall, and J. Davin. A Simple Network Management Protocol (SNMP). Technical Report RFC 1067, IETF, 1988.

Unknown - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M. and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, May 1990.

<u>Unknown - (Correct)</u>

No context found.

Case, J., Fedor, M., Schoffstall, M. and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, May 1990.

Network Working Group S. Waldbusser - Request For Comments (Correct)

h ceee e c e

Citations: Simple Network Management Protocol - Case, Fedor, Schoffstall, Davin (Rese... Page 7 of 7

No context found.

Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, SNMP Research, Performance Systems International, Performance Systems International, MIT Laboratory for Computer Science, May 1990.

Unknown - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol", RFC 1157, SNMP Research, Performance Systems International, Performance Systems International, MIT Laboratory for Computer Science, May 1990.

Unknown - (Correct)

No context found.

Case, J., Fedor, M., Schoffstall, M. and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, May 1990.

<u>Unknown - (Correct)</u>

No context found.

Case, J., Fedor, M., Schoffstall, M. and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, May 1990.

First 50 documents Next 50

CiteSeer.IST - Copyright Penn State and NEC

Network Working Group Request for Comments: 3416

STD: 62

Obsoletes: 1905

Category: Standards Track

Editor of this version:
R. Presuhn
BMC Software, Inc.
Authors of previous version:
J. Case
SNMP Research, Inc.
K. McCloghrie
Cisco Systems, Inc.
M. Rose
Dover Beach Consulting, Inc.
S. Waldbusser
International Network Services
December 2002

Version 2 of the Protocol Operations for the Simple Network Management Protocol (SNMP)

Status of this Memo

This document specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" (STD 1) for the standardization state and status of this protocol. Distribution of this memo is unlimited.

Copyright Notice

Copyright (C) The Internet Society (2002). All Rights Reserved.

Abstract

This document defines version 2 of the protocol operations for the Simple Network Management Protocol (SNMP). It defines the syntax and elements of procedure for sending, receiving, and processing SNMP PDUs. This document obsoletes RFC 1905.

Table of Contents

1. Introduction	3
2. Overview	4
2.1. Management Information	4
2.2. Retransmission of Requests	4
2.3. Message Sizes	4
2.4. Transport Mappings	5
2.5. SMIv2 Data Type Mappings	6
3. Definitions	6
4. Protocol Specification	9
4.1. Common Constructs	9
•	10
4.2.1. The GetRequest-PDU	10
4.2.2. The GetNextRequest-PDU	11
•	12
	14
4.2.3.1. Another Example of Table Traversal	17
•	18
	19
	22
•	23
5. Notice on Intellectual Property	24
•	24
	26
	26
8.1. Normative References	26
8.2. Informative References	27
9. Changes from RFC 1905	28
10. Editor's Address	30
11 Full Copyright Statement	21

1. Introduction

The SNMP Management Framework at the time of this writing consists of five major components:

- An overall architecture, described in STD 62, RFC 3411 [RFC3411].
- Mechanisms for describing and naming objects and events for the purpose of management. The first version of this Structure of Management Information (SMI) is called SMIv1 and described in STD 16, RFC 1155 [RFC1155], STD 16, RFC 1212 [RFC1212] and RFC 1215 [RFC1215]. The second version, called SMIv2, is described in STD 58, RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579] and STD 58, RFC 2580 [RFC2580].
- Message protocols for transferring management information. The first version of the SNMP message protocol is called SNMPv1 and described in STD 15, RFC 1157 [RFC1157]. A second version of the SNMP message protocol, which is not an Internet standards track protocol, is called SNMPv2c and described in RFC 1901 [RFC1901] and STD 62, RFC 3417 [RFC3417]. The third version of the message protocol is called SNMPv3 and described in STD 62, RFC 3417 [RFC3417], RFC 3412 [RFC3412] and RFC 3414 [RFC3414].
- Protocol operations for accessing management information. The first set of protocol operations and associated PDU formats is described in STD 15, RFC 1157 [RFC1157]. A second set of protocol operations and associated PDU formats is described in this document.
- A set of fundamental applications described in STD 62, RFC 3413 [RFC3413] and the view-based access control mechanism described in STD 62, RFC 3415 [RFC3415].

A more detailed introduction to the SNMP Management Framework at the time of this writing can be found in RFC 3410 [RFC3410].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. Objects in the MIB are defined using the mechanisms defined in the SMI.

This document, Version 2 of the Protocol Operations for the Simple Network Management Protocol, defines the operations of the protocol with respect to the sending and receiving of PDUs to be carried by the message protocol.

2. Overview

SNMP entities supporting command generator or notification receiver applications (traditionally called "managers") communicate with SNMP entities supporting command responder or notification originator applications (traditionally called "agents"). The purpose of this protocol is the transport of management information and operations.

2.1. Management Information

The term "variable" refers to an instance of a non-aggregate object type defined according to the conventions set forth in the SMI [RFC2578] or the textual conventions based on the SMI [RFC2579]. The term "variable binding" normally refers to the pairing of the name of a variable and its associated value. However, if certain kinds of exceptional conditions occur during processing of a retrieval request, a variable binding will pair a name and an indication of that exception.

A variable-binding list is a simple list of variable bindings.

The name of a variable is an OBJECT IDENTIFIER which is the concatenation of the OBJECT IDENTIFIER of the corresponding object-type together with an OBJECT IDENTIFIER fragment identifying the instance. The OBJECT IDENTIFIER of the corresponding object-type is called the OBJECT IDENTIFIER prefix of the variable.

2.2. Retransmission of Requests

For all types of request in this protocol, the receiver is required under normal circumstances, to generate and transmit a response to the originator of the request. Whether or not a request should be retransmitted if no corresponding response is received in an appropriate time interval, is at the discretion of the application originating the request. This will normally depend on the urgency of the request. However, such an application needs to act responsibly in respect to the frequency and duration of re-transmissions. See BCP 41 [RFC2914] for discussion of relevant congestion control principles.

2.3. Message Sizes

The maximum size of an SNMP message is limited to the minimum of:

(1) the maximum message size which the destination SNMP entity can accept; and, (2) the maximum message size which the source SNMP entity can generate.

The former may be known on a per-recipient basis; and in the absence of such knowledge, is indicated by transport domain used when sending the message. The latter is imposed by implementation-specific local constraints.

Each transport mapping for the SNMP indicates the minimum message size which a SNMP implementation must be able to produce or consume. Although implementations are encouraged to support larger values whenever possible, a conformant implementation must never generate messages larger than allowed by the receiving SNMP entity.

One of the aims of the GetBulkRequest-PDU, specified in this protocol, is to minimize the number of protocol exchanges required to retrieve a large amount of management information. As such, this PDU type allows an SNMP entity supporting command generator applications to request that the response be as large as possible given the constraints on message sizes. These constraints include the limits on the size of messages which the SNMP entity supporting command responder applications can generate, and the SNMP entity supporting command generator applications can receive.

However, it is possible that such maximum sized messages may be larger than the Path MTU of the path across the network traversed by the messages. In this situation, such messages are subject to fragmentation. Fragmentation is generally considered to be harmful [FRAG], since among other problems, it leads to a decrease in the reliability of the transfer of the messages. Thus, an SNMP entity which sends a GetBulkRequest-PDU must take care to set its parameters accordingly, so as to reduce the risk of fragmentation. In particular, under conditions of network stress, only small values should be used for max-repetitions.

2.4. Transport Mappings

It is important to note that the exchange of SNMP messages requires only an unreliable datagram service, with every message being entirely and independently contained in a single transport datagram. Specific transport mappings and encoding rules are specified elsewhere [RFC3417]. However, the preferred mapping is the use of the User Datagram Protocol [RFC768].

2.5. SMIv2 Data Type Mappings

The SMIv2 [RFC2578] defines 11 base types (INTEGER, OCTET STRING, OBJECT IDENTIFIER, Integer32, IpAddress, Counter32, Gauge32, Unsigned32, TimeTicks, Opaque, Counter64) and the BITS construct. The SMIv2 base types are mapped to the corresponding selection type in the SimpleSyntax and ApplicationSyntax choices of the ASN.1 SNMP protocol definition. Note that the INTEGER and Integer32 SMIv2 base types are mapped to the integer-value selection type of the SimpleSyntax choice. Similarly, the Gauge32 and Unsigned32 SMIv2 base types are mapped to the unsigned-integer-value selection type of the ApplicationSyntax choice.

The SMIv2 BITS construct is mapped to the string-value selection type of the SimpleSyntax choice. A BITS value is encoded as an OCTET STRING, in which all the named bits in (the definition of) the bitstring, commencing with the first bit and proceeding to the last bit, are placed in bits 8 (high order bit) to 1 (low order bit) of the first octet, followed by bits 8 to 1 of each subsequent octet in turn, followed by as many bits as are needed of the final subsequent octet, commencing with bit 8. Remaining bits, if any, of the final octet are set to zero on generation and ignored on receipt.

3. Definitions

```
The PDU syntax is defined using ASN.1 notation [ASN1].
SNMPv2-PDU DEFINITIONS ::= BEGIN
ObjectName ::= OBJECT IDENTIFIER
ObjectSyntax ::= CHOICE {
     simple
                      SimpleSyntax,
     application-wide ApplicationSyntax }
SimpleSyntax ::= CHOICE {
     integer-value
                    INTEGER (-2147483648..2147483647),
                     OCTET STRING (SIZE (0..65535)),
     string-value
     objectID-value OBJECT IDENTIFIER }
ApplicationSyntax ::= CHOICE {
     ipAddress-value
                            IpAddress,
     counter-value
                           Counter32,
     timeticks-value
                           TimeTicks,
     arbitrary-value
                           Opaque,
     big-counter-value
                        Counter64,
     unsigned-integer-value Unsigned32 }
```

```
IpAddress ::= [APPLICATION 0] IMPLICIT OCTET STRING (SIZE (4))
Counter32 ::= [APPLICATION 1] IMPLICIT INTEGER (0..4294967295)
Unsigned32 ::= [APPLICATION 2] IMPLICIT INTEGER (0..4294967295)
Gauge32 ::= Unsigned32
TimeTicks ::= [APPLICATION 3] IMPLICIT INTEGER (0..4294967295)
Opaque ::= [APPLICATION 4] IMPLICIT OCTET STRING
Counter64 ::= [APPLICATION 6]
              IMPLICIT INTEGER (0..18446744073709551615)
-- protocol data units
PDUs ::= CHOICE {
     get-request
                      GetRequest-PDU,
     get-next-request GetNextRequest-PDU,
     get-bulk-request GetBulkRequest-PDU,
                     Response-PDU,
    response
     set-request
                     SetRequest-PDU,
     inform-request InformRequest-PDU,
                    SNMPv2-Trap-PDU,
     snmpV2-trap
     report
                      Report-PDU }
-- PDUs
GetRequest-PDU ::= [0] IMPLICIT PDU
GetNextRequest-PDU ::= [1] IMPLICIT PDU
Response-PDU ::= [2] IMPLICIT PDU
SetRequest-PDU ::= [3] IMPLICIT PDU
-- [4] is obsolete
GetBulkRequest-PDU ::= [5] IMPLICIT BulkPDU
InformRequest-PDU ::= [6] IMPLICIT PDU
SNMPv2-Trap-PDU ::= [7] IMPLICIT PDU
    Usage and precise semantics of Report-PDU are not defined
    in this document. Any SNMP administrative framework making
    use of this PDU must define its usage and semantics.
```

```
Report-PDU ::= [8] IMPLICIT PDU
max-bindings INTEGER ::= 2147483647
PDU ::= SEQUENCE {
        request-id INTEGER (-214783648..214783647),
        error-status
                                    -- sometimes ignored
            INTEGER {
                noError(0),
                tooBig(1),
                noSuchName(2),
                                    -- for proxy compatibility
                badValue(3),
                                    -- for proxy compatibility
                readOnly(4),
                                    -- for proxy compatibility
                genErr(5),
                noAccess(6),
                wrongType(7),
                wrongLength(8),
                wrongEncoding(9),
                wrongValue(10),
                noCreation(11),
                inconsistentValue(12),
                resourceUnavailable(13),
                commitFailed(14),
                undoFailed(15),
                authorizationError(16),
                notWritable(17),
                inconsistentName(18)
            },
        error-index
                                    -- sometimes ignored
            INTEGER (0..max-bindings),
        variable-bindings
                                    -- values are sometimes ignored
            VarBindList
    }
BulkPDU ::=
                                    -- must be identical in
    SEQUENCE {
                                    -- structure to PDU
        request-id
                        INTEGER (-214783648..214783647),
        non-repeaters INTEGER (0..max-bindings),
       max-repetitions INTEGER (0..max-bindings),
        variable-bindings
                                    -- values are ignored
            VarBindList
    }
-- variable binding
```

```
VarBind ::= SEQUENCE {
       name ObjectName,
        CHOICE {
                          ObjectSyntax,
           value
           unSpecified
                          NULL, -- in retrieval requests
                                   -- exceptions in responses
                           [0] IMPLICIT NULL,
           noSuchObject
           noSuchInstance [1] IMPLICIT NULL,
            endOfMibView [2] IMPLICIT NULL
        }
-- variable-binding list
VarBindList ::= SEQUENCE (SIZE (0..max-bindings)) OF VarBind
END
```

4. Protocol Specification

4.1. Common Constructs

The value of the request-id field in a Response-PDU takes the value of the request-id field in the request PDU to which it is a response. By use of the request-id value, an application can distinguish the (potentially multiple) outstanding requests, and thereby correlate incoming responses with outstanding requests. In cases where an unreliable datagram service is used, the request-id also provides a simple means of identifying messages duplicated by the network. Use of the same request-id on a retransmission of a request allows the response to either the original transmission or the retransmission to satisfy the request. However, in order to calculate the round trip time for transmission and processing of a request-response transaction, the application needs to use a different request-id value on a retransmitted request. The latter strategy is recommended for use in the majority of situations.

A non-zero value of the error-status field in a Response-PDU is used to indicate that an error occurred to prevent the processing of the request. In these cases, a non-zero value of the Response-PDU's error-index field provides additional information by identifying which variable binding in the list caused the error. A variable binding is identified by its index value. The first variable binding in a variable-binding list is index one, the second is index two, etc.

SNMP limits OBJECT IDENTIFIER values to a maximum of 128 subidentifiers, where each sub-identifier has a maximum value of 2**32-1.

4.2. PDU Processing

In the elements of procedure below, any field of a PDU which is not referenced by the relevant procedure is ignored by the receiving SNMP entity. However, all components of a PDU, including those whose values are ignored by the receiving SNMP entity, must have valid ASN.1 syntax and encoding. For example, some PDUs (e.g., the GetRequest-PDU) are concerned only with the name of a variable and not its value. In this case, the value portion of the variable binding is ignored by the receiving SNMP entity. The unSpecified value is defined for use as the value portion of such bindings.

On generating a management communication, the message "wrapper" to encapsulate the PDU is generated according to the "Elements of Procedure" of the administrative framework in use. The definition of "max-bindings" imposes an upper bound on the number of variable bindings. In practice, the size of a message is also limited by constraints on the maximum message size. A compliant implementation must support as many variable bindings in a PDU or BulkPDU as fit into the overall maximum message size limit of the SNMP engine, but no more than 2147483647 variable bindings.

On receiving a management communication, the "Elements of Procedure" of the administrative framework in use is followed, and if those procedures indicate that the operation contained within the message is to be performed locally, then those procedures also indicate the MIB view which is visible to the operation.

4.2.1. The GetRequest-PDU

A GetRequest-PDU is generated and transmitted at the request of an application.

Upon receipt of a GetRequest-PDU, the receiving SNMP entity processes each variable binding in the variable-binding list to produce a Response-PDU. All fields of the Response-PDU have the same values as the corresponding fields of the received request except as indicated below. Each variable binding is processed as follows:

(1) If the variable binding's name exactly matches the name of a variable accessible by this request, then the variable binding's value field is set to the value of the named variable.

- (2) Otherwise, if the variable binding's name does not have an OBJECT IDENTIFIER prefix which exactly matches the OBJECT IDENTIFIER prefix of any (potential) variable accessible by this request, then its value field is set to "noSuchObject".
- (3) Otherwise, the variable binding's value field is set to "noSuchInstance".

If the processing of any variable binding fails for a reason other than listed above, then the Response-PDU is re-formatted with the same values in its request-id and variable-bindings fields as the received GetRequest-PDU, with the value of its error-status field set to "genErr", and the value of its error-index field is set to the index of the failed variable binding.

Otherwise, the value of the Response-PDU's error-status field is set to "noError", and the value of its error-index field is zero.

The generated Response-PDU is then encapsulated into a message. If the size of the resultant message is less than or equal to both a local constraint and the maximum message size of the originator, it is transmitted to the originator of the GetRequest-PDU.

Otherwise, an alternate Response-PDU is generated. This alternate Response-PDU is formatted with the same value in its request-id field as the received GetRequest-PDU, with the value of its error-status field set to "tooBig", the value of its error-index field set to zero, and an empty variable-bindings field. This alternate Response-PDU is then encapsulated into a message. If the size of the resultant message is less than or equal to both a local constraint and the maximum message size of the originator, it is transmitted to the originator of the GetRequest-PDU. Otherwise, the snmpSilentDrops [RFC3418] counter is incremented and the resultant message is discarded.

4.2.2. The GetNextRequest-PDU

A GetNextRequest-PDU is generated and transmitted at the request of an application.

Upon receipt of a GetNextRequest-PDU, the receiving SNMP entity processes each variable binding in the variable-binding list to produce a Response-PDU. All fields of the Response-PDU have the same values as the corresponding fields of the received request except as indicated below. Each variable binding is processed as follows:

(1) The variable is located which is in the lexicographically ordered list of the names of all variables which are

Presuhn, et al.

Standards Track

[Page 11]

accessible by this request and whose name is the first lexicographic successor of the variable binding's name in the incoming GetNextRequest-PDU. The corresponding variable binding's name and value fields in the Response-PDU are set to the name and value of the located variable.

(2) If the requested variable binding's name does not lexicographically precede the name of any variable accessible by this request, i.e., there is no lexicographic successor, then the corresponding variable binding produced in the Response-PDU has its value field set to "endOfMibView", and its name field set to the variable binding's name in the request.

If the processing of any variable binding fails for a reason other than listed above, then the Response-PDU is re-formatted with the same values in its request-id and variable-bindings fields as the received GetNextRequest-PDU, with the value of its error-status field set to "genErr", and the value of its error-index field is set to the index of the failed variable binding.

Otherwise, the value of the Response-PDU's error-status field is set to "noError", and the value of its error-index field is zero.

The generated Response-PDU is then encapsulated into a message. If the size of the resultant message is less than or equal to both a local constraint and the maximum message size of the originator, it is transmitted to the originator of the GetNextRequest-PDU.

Otherwise, an alternate Response-PDU is generated. This alternate Response-PDU is formatted with the same values in its request-id field as the received GetNextRequest-PDU, with the value of its error-status field set to "tooBig", the value of its error-index field set to zero, and an empty variable-bindings field. This alternate Response-PDU is then encapsulated into a message. If the size of the resultant message is less than or equal to both a local constraint and the maximum message size of the originator, it is transmitted to the originator of the GetNextRequest-PDU. Otherwise, the snmpSilentDrops [RFC3418] counter is incremented and the resultant message is discarded.

4.2.2.1. Example of Table Traversal

An important use of the GetNextRequest-PDU is the traversal of conceptual tables of information within a MIB. The semantics of this type of request, together with the method of identifying individual instances of objects in the MIB, provides access to related objects in the MIB as if they enjoyed a tabular organization.

In the protocol exchange sketched below, an application retrieves the media-dependent physical address and the address-mapping type for each entry in the IP net-to-media Address Translation Table [RFC1213] of a particular network element. It also retrieves the value of sysUpTime [RFC3418], at which the mappings existed. Suppose that the command responder's IP net-to-media table has three entries:

Interface-Number Network-Address Physical-Address Type

```
1 10.0.0.51 00:00:10:01:23:45 static
1 9.2.3.4 00:00:10:54:32:10 dynamic
2 10.0.0.15 00:00:10:98:76:54 dynamic
```

The SNMP entity supporting a command generator application begins by sending a GetNextRequest-PDU containing the indicated OBJECT IDENTIFIER values as the requested variable names:

The SNMP entity supporting a command responder application responds with a Response-PDU:

The SNMP entity supporting the command generator application continues with:

The SNMP entity supporting the command responder application responds with:

The SNMP entity supporting the command generator application continues with:

The SNMP entity supporting the command responder application responds with:

The SNMP entity supporting the command generator application continues with:

As there are no further entries in the table, the SNMP entity supporting the command responder application responds with the variables that are next in the lexicographical ordering of the accessible object names, for example:

Note how, having reached the end of the column for ipNetToMediaPhysAddress, the second variable binding from the command responder application has now "wrapped" to the first row in the next column. Furthermore, note how, having reached the end of the ipNetToMediaTable for the third variable binding, the command responder application has responded with the next available object, which is outside that table. This response signals the end of the table to the command generator application.

4.2.3. The GetBulkRequest-PDU

A GetBulkRequest-PDU is generated and transmitted at the request of an application. The purpose of the GetBulkRequest-PDU is to request the transfer of a potentially large amount of data, including, but not limited to, the efficient and rapid retrieval of large tables.

Upon receipt of a GetBulkRequest-PDU, the receiving SNMP entity processes each variable binding in the variable-binding list to produce a Response-PDU with its request-id field having the same value as in the request.

For the GetBulkRequest-PDU type, the successful processing of each variable binding in the request generates zero or more variable bindings in the Response-PDU. That is, the one-to-one mapping between the variable bindings of the GetRequest-PDU, GetNextRequest-

PDU, and SetRequest-PDU types and the resultant Response-PDUs does not apply for the mapping between the variable bindings of a GetBulkRequest-PDU and the resultant Response-PDU.

The values of the non-repeaters and max-repetitions fields in the request specify the processing requested. One variable binding in the Response-PDU is requested for the first N variable bindings in the request and M variable bindings are requested for each of the R remaining variable bindings in the request. Consequently, the total number of requested variable bindings communicated by the request is given by N + (M * R), where N is the minimum of: a) the value of the non-repeaters field in the request, and b) the number of variable bindings in the request; M is the value of the max-repetitions field in the request; and R is the maximum of: a) number of variable bindings in the request - N, and b) zero.

The receiving SNMP entity produces a Response-PDU with up to the total number of requested variable bindings communicated by the request. The request-id shall have the same value as the received GetBulkRequest-PDU.

If N is greater than zero, the first through the (N)-th variable bindings of the Response-PDU are each produced as follows:

- (1) The variable is located which is in the lexicographically ordered list of the names of all variables which are accessible by this request and whose name is the first lexicographic successor of the variable binding's name in the incoming GetBulkRequest-PDU. The corresponding variable binding's name and value fields in the Response-PDU are set to the name and value of the located variable.
- (2) If the requested variable binding's name does not lexicographically precede the name of any variable accessible by this request, i.e., there is no lexicographic successor, then the corresponding variable binding produced in the Response-PDU has its value field set to "endOfMibView", and its name field set to the variable binding's name in the request.

If M and R are non-zero, the (N+1)-th and subsequent variable bindings of the Response-PDU are each produced in a similar manner. For each iteration i, such that i is greater than zero and less than or equal to M, and for each repeated variable, r, such that r is greater than zero and less than or equal to R, the (N+((i-1)*R)+r)-th variable binding of the Response-PDU is produced as follows:

- (1) The variable which is in the lexicographically ordered list of the names of all variables which are accessible by this request and whose name is the (i)-th lexicographic successor of the (N + r)-th variable binding's name in the incoming GetBulkRequest-PDU is located and the variable binding's name and value fields are set to the name and value of the located variable.
- (2) If there is no (i)-th lexicographic successor, then the corresponding variable binding produced in the Response-PDU has its value field set to "endOfMibView", and its name field set to either the last lexicographic successor, or if there are no lexicographic successors, to the (N + r)-th variable binding's name in the request.

While the maximum number of variable bindings in the Response-PDU is bounded by N + (M \star R), the response may be generated with a lesser number of variable bindings (possibly zero) for either of three reasons.

- (1) If the size of the message encapsulating the Response-PDU containing the requested number of variable bindings would be greater than either a local constraint or the maximum message size of the originator, then the response is generated with a lesser number of variable bindings. This lesser number is the ordered set of variable bindings with some of the variable bindings at the end of the set removed, such that the size of the message encapsulating the Response-PDU is approximately equal to but no greater than either a local constraint or the maximum message size of the originator. Note that the number of variable bindings removed has no relationship to the values of N, M, or R.
- (2) The response may also be generated with a lesser number of variable bindings if for some value of iteration i, such that i is greater than zero and less than or equal to M, that all of the generated variable bindings have the value field set to "endOfMibView". In this case, the variable bindings may be truncated after the (N + (i * R))-th variable binding.
- (3) In the event that the processing of a request with many repetitions requires a significantly greater amount of processing time than a normal request, then a command responder application may terminate the request with less than the full number of repetitions, providing at least one repetition is completed.

If the processing of any variable binding fails for a reason other than listed above, then the Response-PDU is re-formatted with the same values in its request-id and variable-bindings fields as the received GetBulkRequest-PDU, with the value of its error-status field set to "genErr", and the value of its error-index field is set to the index of the variable binding in the original request which corresponds to the failed variable binding.

Otherwise, the value of the Response-PDU's error-status field is set to "noError", and the value of its error-index field to zero.

The generated Response-PDU (possibly with an empty variable-bindings field) is then encapsulated into a message. If the size of the resultant message is less than or equal to both a local constraint and the maximum message size of the originator, it is transmitted to the originator of the GetBulkRequest-PDU. Otherwise, the snmpSilentDrops [RFC3418] counter is incremented and the resultant message is discarded.

4.2.3.1. Another Example of Table Traversal

This example demonstrates how the GetBulkRequest-PDU can be used as an alternative to the GetNextRequest-PDU. The same traversal of the IP net-to-media table as shown in Section 4.2.2.1 is achieved with fewer exchanges.

The SNMP entity supporting the command generator application begins by sending a GetBulkRequest-PDU with the modest max-repetitions value of 2, and containing the indicated OBJECT IDENTIFIER values as the requested variable names:

The SNMP entity supporting the command responder application responds with a Response-PDU:

The SNMP entity supporting the command generator application continues with:

The SNMP entity supporting the command responder application responds with:

Note how, as in the first example, the variable bindings in the response indicate that the end of the table has been reached. The fourth variable binding does so by returning information from the next available column; the fifth variable binding does so by returning information from the first available object lexicographically following the table. This response signals the end of the table to the command generator application.

4.2.4. The Response-PDU

The Response-PDU is generated by an SNMP entity only upon receipt of a GetRequest-PDU, GetNextRequest-PDU, GetBulkRequest-PDU, SetRequest-PDU, or InformRequest-PDU, as described elsewhere in this document.

If the error-status field of the Response-PDU is non-zero, the value fields of the variable bindings in the variable binding list are ignored.

If both the error-status field and the error-index field of the Response-PDU are non-zero, then the value of the error-index field is the index of the variable binding (in the variable-binding list of the corresponding request) for which the request failed. The first variable binding in a request's variable-binding list is index one, the second is index two, etc.

A compliant SNMP entity supporting a command generator application must be able to properly receive and handle a Response-PDU with an error-status field equal to "noSuchName", "badValue", or "readOnly". (See sections 1.3 and 4.3 of [RFC2576].)

Upon receipt of a Response-PDU, the receiving SNMP entity presents its contents to the application which generated the request with the same request-id value. For more details, see [RFC3412].

4.2.5. The SetRequest-PDU

A SetRequest-PDU is generated and transmitted at the request of an application.

Upon receipt of a SetRequest-PDU, the receiving SNMP entity determines the size of a message encapsulating a Response-PDU having the same values in its request-id and variable-bindings fields as the received SetRequest-PDU, and the largest possible sizes of the error-status and error-index fields. If the determined message size is greater than either a local constraint or the maximum message size of the originator, then an alternate Response-PDU is generated, transmitted to the originator of the SetRequest-PDU, and processing of the SetRequest-PDU terminates immediately thereafter. This alternate Response-PDU is formatted with the same values in its request-id field as the received SetRequest-PDU, with the value of its error-status field set to "tooBig", the value of its error-index field set to zero, and an empty variable-bindings field. This alternate Response-PDU is then encapsulated into a message. If the size of the resultant message is less than or equal to both a local constraint and the maximum message size of the originator, it is transmitted to the originator of the SetRequest-PDU. Otherwise, the snmpSilentDrops [RFC3418] counter is incremented and the resultant message is discarded. Regardless, processing of the SetRequest-PDU terminates.

Otherwise, the receiving SNMP entity processes each variable binding in the variable-binding list to produce a Response-PDU. All fields of the Response-PDU have the same values as the corresponding fields of the received request except as indicated below.

The variable bindings are conceptually processed as a two phase operation. In the first phase, each variable binding is validated; if all validations are successful, then each variable is altered in the second phase. Of course, implementors are at liberty to implement either the first, or second, or both, of these conceptual phases as multiple implementation phases. Indeed, such multiple implementation phases may be necessary in some cases to ensure consistency.

The following validations are performed in the first phase on each variable binding until they are all successful, or until one fails:

- (1) If the variable binding's name specifies an existing or non-existent variable to which this request is/would be denied access because it is/would not be in the appropriate MIB view, then the value of the Response-PDU's error-status field is set to "noAccess", and the value of its error-index field is set to the index of the failed variable binding.
- Otherwise, if there are no variables which share the same OBJECT IDENTIFIER prefix as the variable binding's name, and which are able to be created or modified no matter what new value is specified, then the value of the Response-PDU's error-status field is set to "notWritable", and the value of its error-index field is set to the index of the failed variable binding.
- Otherwise, if the variable binding's value field specifies, according to the ASN.1 language, a type which is inconsistent with that required for all variables which share the same OBJECT IDENTIFIER prefix as the variable binding's name, then the value of the Response-PDU's error-status field is set to "wrongType", and the value of its error-index field is set to the index of the failed variable binding.
- (4) Otherwise, if the variable binding's value field specifies, according to the ASN.1 language, a length which is inconsistent with that required for all variables which share the same OBJECT IDENTIFIER prefix as the variable binding's name, then the value of the Response-PDU's error-status field is set to "wrongLength", and the value of its error-index field is set to the index of the failed variable binding.
- (5) Otherwise, if the variable binding's value field contains an ASN.1 encoding which is inconsistent with that field's ASN.1 tag, then the value of the Response-PDU's error-status field is set to "wrongEncoding", and the value of its error-index field is set to the index of the failed variable binding. (Note that not all implementation strategies will generate this error.)
- (6) Otherwise, if the variable binding's value field specifies a value which could under no circumstances be assigned to the variable, then the value of the Response-PDU's error-status field is set to "wrongValue", and the value of its error-index field is set to the index of the failed variable binding.

- (7) Otherwise, if the variable binding's name specifies a variable which does not exist and could not ever be created (even though some variables sharing the same OBJECT IDENTIFIER prefix might under some circumstances be able to be created), then the value of the Response-PDU's error-status field is set to "noCreation", and the value of its error-index field is set to the index of the failed variable binding.
- (8) Otherwise, if the variable binding's name specifies a variable which does not exist but can not be created under the present circumstances (even though it could be created under other circumstances), then the value of the Response-PDU's errorstatus field is set to "inconsistentName", and the value of its error-index field is set to the index of the failed variable binding.
- (9) Otherwise, if the variable binding's name specifies a variable which exists but can not be modified no matter what new value is specified, then the value of the Response-PDU's error-status field is set to "notWritable", and the value of its error-index field is set to the index of the failed variable binding.
- (10) Otherwise, if the variable binding's value field specifies a value that could under other circumstances be held by the variable, but is presently inconsistent or otherwise unable to be assigned to the variable, then the value of the Response-PDU's error-status field is set to "inconsistentValue", and the value of its error-index field is set to the index of the failed variable binding.
- (11) When, during the above steps, the assignment of the value specified by the variable binding's value field to the specified variable requires the allocation of a resource which is presently unavailable, then the value of the Response-PDU's error-status field is set to "resourceUnavailable", and the value of its error-index field is set to the index of the failed variable binding.
- (12) If the processing of the variable binding fails for a reason other than listed above, then the value of the Response-PDU's error-status field is set to "genErr", and the value of its error-index field is set to the index of the failed variable binding.
- (13) Otherwise, the validation of the variable binding succeeds.

At the end of the first phase, if the validation of all variable bindings succeeded, then the value of the Response-PDU's error-status field is set to "noError" and the value of its error-index field is zero, and processing continues as follows.

For each variable binding in the request, the named variable is created if necessary, and the specified value is assigned to it. Each of these variable assignments occurs as if simultaneously with respect to all other assignments specified in the same request. However, if the same variable is named more than once in a single request, with different associated values, then the actual assignment made to that variable is implementation-specific.

If any of these assignments fail (even after all the previous validations), then all other assignments are undone, and the Response-PDU is modified to have the value of its error-status field set to "commitFailed", and the value of its error-index field set to the index of the failed variable binding.

If and only if it is not possible to undo all the assignments, then the Response-PDU is modified to have the value of its error-status field set to "undoFailed", and the value of its error-index field is set to zero. Note that implementations are strongly encouraged to take all possible measures to avoid use of either "commitFailed" or "undoFailed" - these two error-status codes are not to be taken as license to take the easy way out in an implementation.

Finally, the generated Response-PDU is encapsulated into a message, and transmitted to the originator of the SetRequest-PDU.

4.2.6. The SNMPv2-Trap-PDU

An SNMPv2-Trap-PDU is generated and transmitted by an SNMP entity on behalf of a notification originator application. The SNMPv2-Trap-PDU is often used to notify a notification receiver application at a logically remote SNMP entity that an event has occurred or that a condition is present. There is no confirmation associated with this notification delivery mechanism.

The destination(s) to which an SNMPv2-Trap-PDU is sent is determined in an implementation-dependent fashion by the SNMP entity. The first two variable bindings in the variable binding list of an SNMPv2-Trap-PDU are sysUpTime.0 [RFC3418] and snmpTrapOID.0 [RFC3418] respectively. If the OBJECTS clause is present in the invocation of the corresponding NOTIFICATION-TYPE macro, then each corresponding variable, as instantiated by this notification, is copied, in order,

to the variable-bindings field. If any additional variables are being included (at the option of the generating SNMP entity), then each is copied to the variable-bindings field.

4.2.7. The InformRequest-PDU

An InformRequest-PDU is generated and transmitted by an SNMP entity on behalf of a notification originator application. The InformRequest-PDU is often used to notify a notification receiver application that an event has occurred or that a condition is present. This is a confirmed notification delivery mechanism, although there is, of course, no guarantee of delivery.

The destination(s) to which an InformRequest-PDU is sent is specified by the notification originator application. The first two variable bindings in the variable binding list of an InformRequest-PDU are sysUpTime.0 [RFC3418] and snmpTrapOID.0 [RFC3418] respectively. If the OBJECTS clause is present in the invocation of the corresponding NOTIFICATION-TYPE macro, then each corresponding variable, as instantiated by this notification, is copied, in order, to the variable-bindings field. If any additional variables are being included (at the option of the generating SNMP entity), then each is copied to the variable-bindings field.

Upon receipt of an InformRequest-PDU, the receiving SNMP entity determines the size of a message encapsulating a Response-PDU with the same values in its request-id, error-status, error-index and variable-bindings fields as the received InformRequest-PDU. If the determined message size is greater than either a local constraint or the maximum message size of the originator, then an alternate Response-PDU is generated, transmitted to the originator of the InformRequest-PDU, and processing of the InformRequest-PDU terminates immediately thereafter. This alternate Response-PDU is formatted with the same values in its request-id field as the received InformRequest-PDU, with the value of its error-status field set to "tooBig", the value of its error-index field set to zero, and an empty variable-bindings field. This alternate Response-PDU is then encapsulated into a message. If the size of the resultant message is less than or equal to both a local constraint and the maximum message size of the originator, it is transmitted to the originator of the InformRequest-PDU. Otherwise, the snmpSilentDrops [RFC3418] counter is incremented and the resultant message is discarded. Regardless, processing of the InformRequest-PDU terminates.

Otherwise, the receiving SNMP entity:

(1) presents its contents to the appropriate application;

- (2) generates a Response-PDU with the same values in its request-id and variable-bindings fields as the received InformRequest-PDU, with the value of its error-status field set to "noError" and the value of its error-index field set to zero; and
- (3) transmits the generated Response-PDU to the originator of the InformRequest-PDU.

5. Notice on Intellectual Property

The IETF takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on the IETF's procedures with respect to rights in standards-track and standards-related documentation can be found in BCP-11. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementors or users of this specification can be obtained from the IETF Secretariat.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which may cover technology that may be required to practice this standard. Please address the information to the IETF Executive Director.

6. Acknowledgments

This document is the product of the SNMPv3 Working Group. Some special thanks are in order to the following Working Group members:

Randy Bush
Jeffrey D. Case
Mike Daniele
Rob Frye
Lauren Heintz
Keith McCloghrie
Russ Mundy
David T. Perkins
Randy Presuhn
Aleksey Romanov
Juergen Schoenwaelder
Bert Wijnen

This version of the document, edited by Randy Presuhn, was initially based on the work of a design team whose members were:

Jeffrey D. Case Keith McCloghrie David T. Perkins Randy Presuhn Juergen Schoenwaelder

The previous versions of this document, edited by Keith McCloghrie, was the result of significant work by four major contributors:

Jeffrey D. Case Keith McCloghrie Marshall T. Rose Steven Waldbusser

Additionally, the contributions of the SNMPv2 Working Group to the previous versions are also acknowledged. In particular, a special thanks is extended for the contributions of:

Alexander I. Alten Dave Arneson Uri Blumenthal Doug Book Kim Curran Jim Galvin Maria Greene Iain Hanson Dave Harrington Nguyen Hien Jeff Johnson Michael Kornegay Deirdre Kostick David Levi Daniel Mahoney Bob Natale Brian O'Keefe Andrew Pearson Dave Perkins Randy Presuhn Aleksey Romanov Shawn Routhier Jon Saperia Juergen Schoenwaelder Bob Stewart

Kaj Tesink Glenn Waters Bert Wijnen

7. Security Considerations

The protocol defined in this document by itself does not provide a secure environment. Even if the network itself is secure (for example by using IPSec), there is no control as to who on the secure network is allowed access to management information.

It is recommended that the implementors consider the security features as provided by the SNMPv3 framework. Specifically, the use of the User-based Security Model STD 62, RFC 3414 [RFC3414] and the View-based Access Control Model STD 62, RFC 3415 [RFC3415] is recommended.

It is then a customer/user responsibility to ensure that the SNMP entity is properly configured so that:

- only those principals (users) having legitimate rights can access or modify the values of any MIB objects supported by that entity;
- the occurrence of particular events on the entity will be communicated appropriately;
- the entity responds appropriately and with due credence to events and information that have been communicated to it.

8. References

8.1. Normative References

- [RFC768] Postel, J., "User Datagram Protocol", STD 6, RFC 768, August 1980.
- [RFC2578] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J.,
 Rose, M. and S. Waldbusser, "Structure of Management
 Information Version 2 (SMIv2)", STD 58, RFC 2578, April
 1999.
- [RFC2579] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J.,
 Rose, M. and S. Waldbusser, "Textual Conventions for
 SMIv2", STD 58, RFC 2579, April 1999.

- [RFC2580] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J.,
 Rose, M. and S. Waldbusser, "Conformance Statements for
 SMIv2", STD 58, RFC 2580, April 1999.
- [RFC3411] Harrington, D., Presuhn, R. and B. Wijnen, "An
 Architecture for Describing Simple Network Management
 Protocol (SNMP) Management Frameworks", STD 62, RFC 3411,
 December 2002.
- [RFC3412] Case, J., Harrington, D., Presuhn, R. and B. Wijnen,
 "Message Processing and Dispatching for the Simple
 Network Management Protocol (SNMP)", STD 62, RFC 3412,
 December 2002.
- [RFC3414] Blumenthal, U. and B. Wijnen, "The User-Based Security
 Model (USM) for Version 3 of the Simple Network
 Management Protocol (SNMPv3)", STD 62, RFC 3414, December
 2002.
- [RFC3415] Wijnen, B., Presuhn, R. and K. McCloghrie, "View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)", STD 62, RFC 3415, December 2002.
- [RFC3417] Presuhn, R., Case, J., McCloghrie, K., Rose, M. and S.
 Waldbusser, "Transport Mappings for the Simple Network
 Management Protocol", STD 62, RFC 3417, December 2002.
- [RFC3418] Presuhn, R., Case, J., McCloghrie, K., Rose, M. and S.
 Waldbusser, "Management Information Base (MIB) for the
 Simple Network Management Protocol (SNMP)", STD 62, RFC
 3418, December 2002.
- [ASN1] Information processing systems Open Systems
 Interconnection Specification of Abstract Syntax
 Notation One (ASN.1), International Organization for
 Standardization. International Standard 8824, December
 1987.

8.2. Informative References

[FRAG] Kent, C. and J. Mogul, "Fragmentation Considered Harmful," Proceedings, ACM SIGCOMM '87, Stowe, VT, August 1987.

Presuhn, et al.

Standards Track

[Page 27]

- [RFC1212] Rose, M. and K. McCloghrie, "Concise MIB Definitions", STD 16, RFC 1212, March 1991.
- [RFC1213] McCloghrie, K. and M. Rose, Editors, "Management Information Base for Network Management of TCP/IP-based internets: MIB-II", STD 17, RFC 1213, March 1991.
- [RFC1215] Rose, M., "A Convention for Defining Traps for use with the SNMP", RFC 1215, March 1991.

- [RFC2863] McCloghrie, K. and F. Kastenholz, "The Interfaces Group MIB", RFC 2863, June 2000.
- [RFC2914] Floyd, S., "Congestion Control Principles", BCP 41, RFC 2914, September 2000.
- [RFC3410] Case, J., Mundy, R., Partain, D. and B. Stewart,
 "Introduction and Applicability Statements for InternetStandard Management Framework", RFC 3410, December 2002.

9. Changes from RFC 1905

These are the changes from RFC 1905:

- Corrected spelling error in copyright statement;
- Updated copyright date;
- Updated with new editor's name and contact information;
- Added notice on intellectual property;

- Cosmetic fixes to layout and typography;
- Added table of contents;
- Title changed;
- Updated document headers and footers;
- Deleted the old clause 2.3, entitled "Access to Management Information";
- Changed the way in which request-id was defined, though with the same ultimate syntax and semantics, to avoid coupling with SMI. This does not affect the protocol in any way;
- Replaced the word "exception" with the word "error" in the old clause 4.1. This does not affect the protocol in any way;
- Deleted the first two paragraphs of the old clause 4.2;
- Clarified the maximum number of variable bindings that an implementation must support in a PDU. This does not affect the protocol in any way;
- Replaced occurrences of "SNMPv2 application" with "application";
- Deleted three sentences in old clause 4.2.3 describing the handling of an impossible situation. This does not affect the protocol in any way;
- Clarified the use of the SNMPv2-Trap-Pdu in the old clause 4.2.6. This does not affect the protocol in any way;
- Aligned description of the use of the InformRequest-Pdu in old clause 4.2.7 with the architecture. This does not affect the protocol in any way;
- Updated references;
- Re-wrote introduction clause;
- Replaced manager/agent/SNMPv2 entity terminology with terminology from RFC 2571. This does not affect the protocol in any way;
- Eliminated IMPORTS from the SMI, replaced with equivalent inline ASN.1. This does not affect the protocol in any way;

Presuhn, et al.

Standards Track

[Page 29]

- Added notes calling attention to two different manifestations of reaching the end of a table in the table walk examples;
- Added content to security considerations clause;
- Updated ASN.1 comment on use of Report-PDU. This does not affect the protocol in any way;
- Updated acknowledgments section;
- Included information on handling of BITS;
- Deleted spurious comma in ASN.1 definition of PDUs;
- Added abstract;
- Made handling of additional variable bindings in informs consistent with that for traps. This was a correction of an editorial oversight, and reflects implementation practice;
- Added reference to RFC 2914.

10. Editor's Address

Randy Presuhn BMC Software, Inc. 2141 North First Street San Jose, CA 95131 USA

Phone: +1 408 546 1006

EMail: randy_presuhn@bmc.com

11. Full Copyright Statement

Copyright (C) The Internet Society (2002). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Acknowledgement

Funding for the RFC Editor function is currently provided by the Internet Society.

IEEE HOME | SEARCH IEEE | SHOP | WEB ACCOUNT | CONTACT IEEE



Publications/Services Standards Conferences Welcome **United States Patent and Trademark Office** » Se **Quick Links** FAQ Terms IEEE Peer Review Welcome to IEEE Xplore* Your search matched 3 of 1114111 documents. O- Home A maximum of 500 results are displayed, 15 to a page, sorted by Relevance ()- What Can Descending order. | Access? O- Log-out **Refine This Search:** You may refine your search by editing the current search expression or entering **Tables of Contents** new one in the text box. ()- Journals pdu<and>format Search & Magazines ☐ Chečk to search within this result set O- Conference **Proceedings Results Key:** ()- Standards JNL = Journal or Magazine CNF = Conference STD = Standard Search-()- By Author MPEG-2 over ATM: system design issues O- Basic Varma, S.; Compcon '96. 'Technologies for the Information Superhighway' Digest of O- Advanced Papers , 25-28 Feb. 1996 ()- CrossRef Pages: 26 - 31 Member Services [Abstract] [PDF Full-Text (444 KB)] **IEEE CNF** O- Join IEEE)- Establish IEEE 2 An object-oriented model for protocol design Web Account Shung-Bin Yan; Feng-Jian Wang; ()- Access the Technology of Object-Oriented Languages, 1997. TOOLS 24. Proceedings, Se **IEEE Member** 1997 **Digital Library** Pages:12 - 21 IEEE Enterprise [Abstract] [PDF Full-Text (492 KB)] **IEEE CNF** O- Access the **IEEE Enterprise** 3 Using SNMP to manage networks **File Cabinet** Drake, P.; Designing Resilient Architectures, IEE Colloquium on , 15 Nov 1991 Print Format Pages: 2/1 - 2/4

Home | Log-out | Journals | Conference Proceedings | Standards | Search by Author | Basic Search | Advanced Search | Join IEEE | Web Account |
New this week | OPAC Linking Information | Your Feedback | Technical Support | Email Alerting | No Robots Please | Release Notes | IEEE Online
Publications | Help | FAQ | Terms | Back to Top

IEE CNF

f

[PDF Full-Text (228 KB)]

Copyright © 2004 IEEE — All rights reserved

[Abstract]